

KUWES WIRE & CABLE

DATA SHEET & TEST REPORT

ITEM NO.: LIFT A-C6

COMMODITY: LIFT CABLE UTP CAT.6 + 2C MESSENGER

SIZE: 24AWG×4P + 20AWG×2C

DATE: 2017 / 06 / 02

Test Item	Specification	
LIFT CABLE UTP CAT.6		
Conductor(I)	SIZE	24AWG
	Material	BC
	Construction	7/0.20±0.008 mm
Insulation	STD. Thickness	0.21 mm
	MIN. Thickness	0.18 mm
	Diameter	0.95±0.05 mm
	Material	PE
	Color	BLUE / WHITE with BLUE
		ORANGE / WHITE with ORANGE
GREEN / WHITE with GREEN		
BROWN / WHITE with BROWN		
Twisted	Construction	24AWG×2C
Strand	Construction	24AWG×4P + Filler
2C MESSENGER		
Conductor(II)	SIZE	20AWG
	Material	STEEL WIRE
	Construction	19/0.20±0.008 mm
Jacket	REF. Thickness	0.9+1.3+0.9 mm
	Diameter	3.0+7.0+3.0±0.10 mm
	Material	P.V.C.
	Color	BLACK

KUWES WIRE & CABLE

DATA SHEET & TEST REPORT

MARKING	KUWES COMMUNICATION LIFT UTP CAT.6 CABLE + STEEL WIRE SUPPORT, MADE IN TAIWAN 6957 (001M~305M)
----------------	---

CONSTRUCTION DRAWING

